



引领至优未来

Lead to Excellent Future

面板灯|线性灯|大吊灯|天花灯

Panel light•linear light•Pendent Light•Ceiling light



恒照度面板灯

Constant illumination panel light

功能键/Function key

USB充电口/USB

• 恒照度/Constant illumination;

• 集成驱动器/Integrated driver。

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-PA3E/H-6030CW/W/WW-CC-24W	24	100	DC24-28V	600	2700-6000
EX-PA3E/H-6060CW/W/WW-CC-36W	36	100	DC24-28V	900	2700-6000
EX-PA3E/H-6262CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-PA3E/H-12030CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000

低眩光面板灯

Anti-Glare panel light

UGR<19

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-PLGH-3030CW/W/WW-CC-12W	12	100	DC24-28V	300	2700-6000
EX-PLGH-6030CW/W/WW-CC-24W	24	100	DC24-28V	600	2700-6000
EX-PLGH-6060CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-PLGH-6262CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-PLGH-12030CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000

无边面板灯

Frameless panel light

• 专利设计/Patent design;

• 无暗区/No dark area。

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-NPA3-3030CW/W/WW-CC-12W	11	100	DC24-28V	300	2700-6000
EX-NPA3-6030CW/W/WW-CC-24W	22	100	DC24-28V	600	2700-6000
EX-NPA3-6060CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-NPA3-6262CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-NPA3-12030CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000

防水面板灯

Waterproof panel light

• 结构防水/Waterproof structure;

• 非灌胶工艺/No silicon seal process。

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-PEW-3030CW/W/WW-CC-11W	11	100	DC30-40V	300	2700-6000
EX-PEW-6030CW/W/WW-CC-22W	24	100	DC30-40V	600	2700-6000
EX-PEW-6060CW/W/WW-CC-42W	36	100	DC30-40V	900	2700-6000
EX-PEW-12030CW/W/WW-CC-42W	36	100	DC30-40V	900	2700-6000

DALI感应面板灯(人体感应+光感)

IR &Light Sensitive Integrated DALI Panel Light

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-DIR-3030W-CC-18W	18	100	DC24-28V	300	2700-6000
EX-DIR-6030W-CC-22W	22	100	DC24-28V	600	2700-6000
EX-DIR-6060W-CC-36W	36	100	DC33-38V	900	2700-6000
EX-DIR-6262W-CC-36W	36	100	DC33-38V	900	2700-6000
EX-DIR-12030W-CC-36W	36	100	DC33-38V	900	2700-6000

高光效面板灯

High efficiency panel light

>130lm/W

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-PA3H-3030CW/W/WW-CC-12W	12	120	DC24-28V	300	2700-6000
EX-PA3H-6030CW/W/WW-CC-24W	24	130	DC24-28V	600	2700-6000
EX-PA3H-6060CW/W/WW-CC-36W	36	130	DC33-38V	900	2700-6000
EX-PA3H-6262CW/W/WW-CC-36W	36	130	DC33-38V	900	2700-6000
EX-PA3H-12030CW/W/WW-CC-36W	36	130	DC33-38V	900	2700-6000

窄边面板灯

Thin brim panel light

4mm

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-EPA3-3030CW/W/WW-CC-12W	11	100	DC24-28V	300	2700-6000
EX-EPA3-6030CW/W/WW-CC-24W	22	100	DC24-28V	600	2700-6000
EX-EPA3-6060CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-EPA3-6262CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-EPA3-12030CW/W/WW-CC-36W	36	100	DC33-38V	900	2700-6000
EX-EPA3-12060CW/W/WW-CC-48W	60	100	DC33-38V	1450	2700-6000

欧式经典面板灯

Europe classic panel light

型 号 Model	功率 Power (W)±10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-PE2-3030CW/W/WW-CC-11W	11	70	DC18-27V	400	2700-6000
EX-PE2-6030CW/W/WW-CC-22W	22	70	DC30-42V	540	2700-6000
EX-PE2-6060CW/W/WW-CC-36W	36	80	DC24-34V	1050	2700-6000
EX-PE2-12030CW/W/WW-CC-42W	42	80	DC24-34V	1250	2700-6000
EX-PE2-12060CW/W/WW-CC-60W	60	80	DC27-42V	1500	2700-6000
EX-PE2-12060CW/W/WW-CC-85W	85	80	DC27-42V	2100	2700-6000



荣誉资质
Quailfied Honor



工程案例
Project



天花灯-皓月系列
Ultra thin ceiling light-Selene series



型号 Model	功率 Power (W) ± 10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-CL-R095RGB/CW/W/WW-24V-7W	7	50	DC24V	290	2700-6000
EX-CL-R140RGB/CW/W/WW-24V-10W	10	70	DC24V	410	2700-6000
EX-CL-R170CW/W/WW-24V-14W	14	70	DC24V	580	2700-6000
EX-CL-R200RGB/CW/W/WW-24V-16W	16	75	DC24V	660	2700-6000
EX-CL-R275CW/W/WW-24V-27W	27	70	DC24V	1120	2700-6000
EX-CL-R330RGB/CW/W/WW-24V-34W	34	70	DC24V	1410	2700-6000

天花灯-天宇系列
Ultra thin ceiling light-Zenith series



型号 Model	功率 Power (W) ± 10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-CL-L100RGB/CW/W/WW-24V-6W	6	56	DC24V	250	2700-6000
EX-CL-L150CW/W/WW-24V-11W	11	60	DC24V	450	2700-6000
EX-CL-L180RGB/CW/W/WW-24V-17W	17	60	DC24V	700	2700-6000
EX-CL-L220CW/W/WW-24V-23W	23	70	DC24V	950	2700-6000
EX-CL-L250CW/W/WW-24V-28W	28	70	DC24V	1160	2700-6000
EX-CL-L330RGB/CW/W/WW-24V-36W	36	60	DC24V	1500	2700-6000

大吊灯
Pendent Light



型号 Model	功率 Power (W) ± 10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
LD-DR-R58024-W	33	80	AC220V	/	3000-6000
LD-DR-R73024-W	38	80	AC220V	/	3000-6000
LD-DR-R85024-W	85	80	AC220V	/	3000-6000

玉盘灯
Ceiling light-Gem series



型号 Model	功率 Power (W) ± 10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
EX-DL-YP-A	9.5	80	AC220V	400	3000/4000/6000
EX-DL-YP-B	13.5	80	AC220V	400	3000/4000/6000
EX-DL-YP-C	18	80	AC220V	400	3000/4000/6000

线性灯
Linear light
LS5070



型号 Model	功率 Power (W) ± 10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
LD-LS5070-40W-827/830/840/857-D	40	85	AC220V	/	2700/3000/4000/5700

线性灯
Linear light
LS3567



型号 Model	功率 Power (W) ± 10%	光效 LPW (Lm/W)	输入电压范围 Input voltage (V)	电流 Current (mA)	色温 CCT (K)
LD-LS3567-20W-827/830/840/857-D	20	80	AC220V	/	2700/3000/4000/5700