SHENZHEN LEDMY CO.,LTD

SHENZHEN Marketing Center Room1503-1505, Block 2, Excellence City, Zhongkang Road, Futian District, Shenzhen City, Guangdong Province, PRC 518049

DONGGUAN Manufacturing Center LEDMY Industrial Park, Tongren Road, Longbeiling Industrial Zone, Tangxia Town, Dongguan City, Guangdong Province, PRC 523715


JIANGMEN Manufacturing Center NO. 3 Huahui Road, Waihai Street, Jianghai District, Jiangmen City, Guangdong Province, China, PRC 529000

360° SERIES

Ledmy

www.ledmy.com





Inclusive

360° Requalify spaces, create social and engaging landscapes. Uniform light emission, arbitrary cut position. Use your imagination and creativity to show more possibilities.







R18 White




- Matte oil material used on the surface, with excellent wear resistance, no dust, Soft and smooth feel of hand touch.
- 360° lighting, surface illuminate uniformly without any dark area.
- It can be bent freely, with superior flexibility & wide application.
- IP65, environmental-friendly silicone material, salt and alkali resistant, UV resistant, flame retardant.



	3000K		ΟΟΚ	
360° R18	3 11W \	White		
FEN11WR-F	95-G1-28A	H9x 24V360D	R18L05	
Voltage		DC24V		
Power		11W/M 3.35W,	ft	
CRI		90 (2835LED)	
Led Qty		360LEDs/M		
Cutting Len	gth	/		
Waterproof	grade	IP65		
Diameter		18mm		
Color Temp	erature (Lu	mens Per Mete)	
0 2700K	- 3000K	4000 K	0 6000К	
740lm	770lm	780lm	780lm	

Note:'x' (CCT) ="27"(2700K) / "30"(3000K) / "40"(4000K) / "50"(5000K) / "60"(6000K), Please contact us for more information.


Dimension



For more product accessories, please refer to the product specification.



R23 RGB



3 years warrant

(ŲL)

120°

LM80


ErP

IP65

CE

- Matte oil material used on the surface, with excellent wear resistance, no dust, Soft and smooth feel of hand touch.
- 360° lighting, surface illuminate uniformly without any dark area.
- It can be bent freely, with superior flexibility & wide application. • IP65, environmental-friendly silicone material, salt and alkali
- resistant, UV resistant, flame retardant.

5050mm 198.82"





For more product accessories, please refer to the product specification.

FEN20CR	-P5-G138Z	RGB 24V240D R23L05
Voltage		DC24V
Power		20W/M 6.09W/ft
CRI		- (3838LEDs)
Led Qty		240LEDs/M
Cutting Le	ngth	/
Waterproo	of grade	IP65
Diameter		23mm
Color Temperature (I		umens Per Meter)
●R	●G	●B
157lm	407lm	83lm

Note:'x' (CCT) ="27"(2700K) / "30"(3000K) / "40"(4000K) / "50"(5000K) / "60"(6000K), Please contact us for more information.

Dimension

350MM 13.77"

Clips


RGB

360° R23 20W RGB

22mm 0.86'

360° Series

R23 SPI



- Matte oil material used on the surface, with excellent wear resistance, no dust, Soft and smooth feel of hand touch.
- 360° lighting, surface illuminate uniformly without any dark area.
- It can be bent freely, with superior flexibility & wide application.IP65, environmental-friendly silicone material, salt and alkali
- resistant, UV resistant, flame retardant.

IP65	(years warranty	120°	LM80	ErP
CE		R	DIMMABLE	


RGB

360° R23 18W DMX

FEN18DR-P5	5-G1 50ZI	RGB 24VS168D R23L05
Voltage		DC24V
Power		18W/M 5.48W/ft
CRI		/ (5050LEDs)
Led Qty		168LEDs/M
Cutting Leng	jth	/
Waterproof g	grade	IP65
Diameter		23mm
Color Temperature (Lumens Per Meter)		
●R	●G	●B
133lm	350lm	55lm

Note:'x' (CCT) ="27"(2700K) / "30"(3000K) / "40"(4000K) / "50"(5000K) / "60"(6000K), Please contact us for more information.


Dimension



Installation

360° Series has a relatively complete range of product accessories.It can play its product characteristics in every scene. Expand more possibilities.


R18/R23 Clip installation



Installation steps

Accessories in the package


Assistive tool



R18


R18 Clip

R23 Clip





10 pcs

11111 10 pcs



R23





R18/R23 Vertical hanging installation kit


804-01-0333/804-01-0328





Installation steps

Accessories in the package


Assistive tool















5











æ





R18 Single end Surface mounted installation kit 804-01-0334



Installation steps

Accessories in the package


1 pcs


1 pcs/1m


¥¥

2 pcs

Assistive tool























R18 Both end Surface mounted installation kit 804-01-0335





22


Installation steps


Accessories in the package


Assistive tool















R23 Single end Surface mounted installation kit 804-01-0329



Installation steps

Accessories in the package Assistive tool łÿ Please read carefully before installation and use, and use it in the correct way. The following tools are required to assist with the installation. 1 pcs 1 pcs . 1 pcs/1m ¥¥ T T T T T T T T ĨĨ 1 pcs 2 pcs 8 pcs 2 pcs 3 2 5 6 c.Installation kit ΙT. b.Expansion bolts 4 Н 8 9 straight feed Side feed Side feed or straight feed meet various demands.


R23 Single end Surface mounted installation kit 804-01-0329





Installation steps


Accessories in the package


Assistive tool
















R23 End to end connection installation kit




Installation steps


Accessories in the package


















R23 Horizontal Vertical Suspension Mounting Kit 804-01-0332



Installation steps


Accessories in the package

-2 pcs


1 pcs/1m


2 pcs


Assistive tool




750mm









, 750mm ,

2

Φ6mm

